

SHIP TO	Name:		Acct. No.:		Department Name:			P.O. Number:		
	Address:					Address:			Job Number:	
	City:		State:		Zip:		City:		State: Zip:	
	Phone:		Fax:		Contact:		Apparatus Number:			Today's Date:

FINAL DESTINATION OF SYSTEM

1600 SERIES Automatic Proportioner			
QTY.	DESCRIPTION	NPT, BSP or VIC	12V or 24V
	Model 1600—with 1-1/2" flowmeter	(PLEASE CHOOSE ONE)	(PLEASE CHOOSE ONE)
	Model 1600—with 2" flowmeter		12V
	Model 1601—with 1-1/2" flowmeter 1" ID Bore	NPT	24V
	Model 1601—with 1-1/2" flowmeter	BSP	
	Model 1601—with 2" flowmeter		
	Model 1600—with Manifold	1.5" NPT	
	Model 1601—with Manifold	2" VIC	
1600 SERIES OPTIONS (PLEASE CHOOSE ONE)			
	Remote Start / Stop		English
	Remote Simulated Flow		Australian
	CAFS Power-Link Switch		

Turbo Stream	
QTY.	DESCRIPTION
	S108-4008 High Pressure System
	S108-4008H HP System w/ Honda

Power-Fill Foam Refill Systems	
QTY.	DESCRIPTION
	DC Powered System
	3435-0134—Onboard Mounting 12V
	3435-0135—Onboard Mounting 24V
	AC Powered System
	3435-0118—Complete Portable 110V
	3435-0120—Panel Kit

Models require one low-level tank sensor and main waterway check valve. See Required Accessories.

2000 SERIES Automatic Proportioner				
QTY.	DESCRIPTION	12V or 24V	CONTROL MODULE	Y-STRAINER
	Model 2001	(PLEASE CHOOSE ONE)	(PLEASE CHOOSE ONE)	(PLEASE CHOOSE ONE)
	Model 2002	12V	Standard	3/4"
	Model 2002HP	24V	Advanced Feature Controller (AFC)	1"
	Model 2024	24V Only	Japanese	3350-0144

Models require one low-level tank sensor, main waterway check valve and one flowmeter tee assembly. See REQUIRED ACCESSORIES.

All 24 volt systems are calibrated in liters.

REQUIRED ACCESSORIES					
FLOWMETER AND TEE			MAIN WATERWAY CHECK VALVE		
QTY.	DESCRIPTION	NPT or BSP	QTY.	DESCRIPTION	
	2660-0030 Flowmeter Tee Assembly—1-1/2" x 1"	NPT BSP	STAINLESS STEEL BODY/STAINLESS STEEL COMPONENTS		
	2660-0031 Flowmeter Tee Assembly—1-1/2"				3320-1001—1-1/2" NPT
	2660-0032 Flowmeter Tee Assembly—2"				3320-1002—2" NPT
	2660-0033 Flowmeter Tee Assembly—2-1/2"				3320-1003—2-1/2" NPT
	2660-0034 Flowmeter Tee Assembly—3"				3320-1004—3" NPT
	2660-0035 Flowmeter Tee Assembly—4"				3320-1005—4" NPT
	2660-0044 Insertion Flowmeter	2" NPT	STAINLESS STEEL BODY/STAINLESS STEEL COMPONENTS VICTAULIC ENDS		
	2660-0059 Insertion Flowmeter (Stainless Steel)	2" NPT			3320-0069—1 1/2" Pipe
	2660-0056 Paddlewheel Flowmeter, without tee	N/A			3320-0070—2" Pipe
	1600-0062 Retaining Pin (Paddlewheel)	N/A			3320-0071—2 1/2" Pipe
STAINLESS STEEL MANIFOLD					3320-0072—3" Pipe
QTY.	DESCRIPTION				3320-0073—4" Pipe
	2660-0051 Flowmeter/Check Valve — 1-1/2"	VIC ONLY			
	2660-0052 Flowmeter/Check Valve — 2"				
	2660-0053 Flowmeter/Check Valve — 2-1/2"				
	2660-0054 Flowmeter/Check Valve — 3"				
	2660-0055 Flowmeter/Check Valve — 4"				
LOW-LEVEL TANK SENSOR			<p>FAX for Fast Delivery: (816) 892-3178 Phone: (800) 533-9511 Email: foampro@fireresearch.com</p>		
QTY.	DESCRIPTION				
	2510-0028 Low-Level Tank Sensor—Top/Bottom Mount				
	2510-0032 Low-Level Tank Sensor—Side Mount				
	2400-0113 Bulkhead Fitting for Side Mount Sensor				

SINGLE-POINT 1600 & 2000 OPTIONAL ACCESSORIES

MANUAL CONCENTRATE MANAGEMENT SYSTEM

QTY.	DESCRIPTION
	3435-0079 Selector Valve

Requires one additional low-level sensor. See REQUIRED ACCESSORIES.

ELECTRONIC CONCENTRATE MANAGEMENT SYSTEM

QTY.	DESCRIPTION
	3435-0132 12 volt Selector Valve Dual-Tank
	3435-0133 24 volt Selector Valve Dual-Tank
	3435-0154 12 volt 1-1/2" Selector Valve Dual-Tank
	3435-0162 24 volt 1-1/2" Selector Valve Dual Tank
	3435-0184 12 volt 1" Single Tank with OBPU
	3435-1006, 12 Volt, 1 1/2" Single Tank with OBPU
	3435-1003, 12 Volt, 1" - Dual Tank with OBPU
	3435-1009, 12 Volt, 1 1/2" - Dual Tank with OBPU

Requires one additional low-level sensor. See REQUIRED ACCESSORIES.

MULTIFLO INTERFACE MODULE

QTY.	DESCRIPTION
	2527-0140 MultiFlo Module

Requires one to three additional flowmeters (see REQUIRED ACCESSORIES) and an equal number of flowmeter cables (see OTHER ACCESSORIES).

DUAL INJECTION SELECTOR

QTY.	DESCRIPTION
	3435-0101 24 Volt Dual Injection Selector
	3435-0107 12 Volt Dual Injection Selector

Requires one MultiFlo interface module (see OPTIONAL ACCESSORIES), two flowmeters, and two main waterway check valves (see REQUIRED ACCESSORIES).

SOLID STATE CONTACTOR

QTY.	DESCRIPTION
	2510-0043 7-32 Volts, 75 AMP Continuous, 1000 AMP Surge

REMOTE START/STOP SWITCH

QTY.	DESCRIPTION
	3435-0155 Remote Start/Stop Switch

SYSTEM SCHEMATIC PLACARDS

QTY.	DESCRIPTION
	6032-0015 Single-Tank
	6032-0016 Dual-Tank

SYSTEM RATING PLACARDS

QTY.	DESCRIPTION
	6032-0018 Model 1600
	6032-0019 Model 1601
	6032-0020 Model 2001
	6032-0021 Model 2002
	6032-0035 Model 2002HP
	6032-0055 Model 2024

FOAM TANKS

QTY.	DESCRIPTION
	1530-0005 8 Gallon Poly Foam Tank
	1530-0012 12 Gallon Poly Foam Tank
	1530-0022 20 Gallon Poly Foam Tank
Replacement Caps	
	1530-0027 8 Gallon Replacement Tank Cap
	1530-0019 12 Gallon Replacement Tank Cap
	1530-0023 20 Gallon Replacement Tank Cap

SINGLE TANK FLUSH KITS

QTY.	DESCRIPTION
	3430-0834 Internal Flush Kit
	3430-0835 External Flush Kit

CAFS SWITCH

QTY.	DESCRIPTION
	2510-0063 Power-Link

OTHER ACCESSORIES

QTY.	DESCRIPTION
	2520-0040R Control Cable 4 pin (Dual-Tank)
	2520-0042 Tank Sensor Cable
	2520-0045 Flowmeter Cable - 6'
	2520-0046 Flowmeter Cable - 12'
	2520-0047 Flowmeter Cable - 20'
	2520-0048 Control Cable - 6'
	2520-0049 Control Cable - 12'
	2520-0050 Control Cable - 20'
	2520-0063 Flowmeter Cable 1.5'
	2520-0065 Remote Start Control Cable 4 pin
	2520-0091 Control Cable Dual-Tank 12' (6 pin AFC)
	3320-0055 Injector Check Valve 1/2"
	3320-0041 Injector Check Valve 1"
	3320-0046 Check Valve (Dual-Tank) 3/4"
	3350-0143 Y-Strainer 3/4"
	3350-0144 Y-Strainer 1"
	3430-0351 RFI/EMI Suppression Kit (Control cable)
	3430-0353 RFI/EMI Suppression Kit (Flowmeter cable)
	3800-0084 Replacement Y-Strainer Screens 3/4"
	3800-0085 Replacement Y-Strainer Screens 1"

TEST AND CALIBRATION KITS

QTY.	DESCRIPTION
	3430-0830 NFPA Test & Calibration Kit



A Safe Fleet Brand

26 Southern Blvd. • Nesconset, NY 11767 USA
Phone 800-645-0074 • FAX 816-892-3178
www.fireresearch.com