inView 360 HD Driver's Daily Pre-Trip Checklist



At the beginning of each shift/day, please check the following to ensure they are working properly.

- Turn the vehicle on > 360 HD system turns on

1) Check Cameras

- Verify that the Default Live View (3600 + Left Cam) displays after startup.
- Use the Driver/View (green) button to cycle through all 6 views on the monitor:
 - Top + Left Top + Front Top View
 - Top + Right Top + Back 4 Cam Split

2) Check Signals

- Activate left turn signal > Monitor displays the left camera view.
- Activate right turn signal > Monitor displays the right camera view.
- Place the vehicle in reverse > Monitor displays rear camera view with back-up lines.

3) Check Events*

- Press the Event/Panic (red) button > Verify that "Event Recorded" appears on on the monitor.
 - * You might not want to press this button every time you start up the vehicle, as it would result in multiple "panic" events being recorded.

4) Check Outriggers*

- Press the Outrigger/Overlay (black) button > Verify that red bars appear on the 3600 image
 - * If your vehicle has outriggers but you do not see overlays, contact your administrator.

FRC Customer Service and Product Support:

(8am to 5pm EST weekdays)

- Main Phone: 631.724.8888
- · Fax: 631.360.9727 (24 hours)
- Website: Contact FRC





SD Card Compression Table

Compression Modes	Video Clip File Size Guidelines	Recording Length (hrs)	
		128 GB	256 GB
2 Mbps	4.3 GB / 4 Cameras / hr	30 hours	60 hours
4 Mbps	8.5 GB / 4 Cameras / hr	15 hours	30 hours

These guidelines are subject to compression variations. Data can be extrapolated for other SD sizes.



© Safe Fleet | May 2020 | All rights reserved Document Number: XE-SNB100-C00-DRIVER-R0A